

■ Product Datasheet

HFU-B2315AN

Pressurized Outside to In / Dead-end Filtration Ultrafiltration (UF) Membrane Module

The HFU-B2315AN module features Toray's proven durable PVDF hollow fiber membrane with a high packing density per module resulting in a compact system design and lower capital footprint.

Membrane Characteristics		Units	Value
Membrane Material			PVDF (Polyvinylidene fluoride)
Nominal Pore Size		μm	0.01
Outer Membrane Surface Area		m ² (ft ²)	60 (646)
Operating Parameters		Units	Value
Maximum Feed water / Filtrate Flow		m ³ /h (gpm)	10.0 (44)
Maximum Backwash Flow		m ³ /h (gpm)	11.2 (49)
Maximum Air Flow		Nm ³ /h (scfm)	6.7 (3.9)
Maximum Inlet Pressure		kPa (psi)	300 (43.5)
Maximum Backwash Pressure		kPa (psi)	300 (43.5)
Normal Operating Transmembrane Pressure		kPa (psi)	0–200 (0–29)
Operating Temperature Range		°C (°F)	0–40 (32–104)
pH Range	During Filtration		1–10
	During Cleaning		0–12

*Please contact Toray for operating manual and preliminary design, as capacity per module is highly dependent on feed water quality.



Product Certifications & Compliances

- NSF/ANSI 61 for drinking water applications
- NSF/ANSI 419 to comply with the U.S. EPA's Long Term 2 Enhanced Surface Water Treatment Rule (LT2ESWTR), which allows membrane manufacturers to prove Cryptosporidium reduction.



Applications

Drinking water, Industrial process water, Pretreatment for seawater RO desalination, Tertiary wastewater

■ Product Datasheet

HFU-B2315AN


Pressurized Outside to In / Dead-end Filtration Ultrafiltration (UF) Membrane Module

Dimensions and Weight		Unit	Value
Diameter		mm (in)	178 (7.01)
Length		mm (ft)	2,332 (7.651)
Weight	Full of Water	kg (lbs)	65 (143)
	After Draining	kg (lbs)	35 (77)

Connections	Value
(A) Filtrate Outlet	50A
(B) Air Outlet	Φ57.91 mm x P3
(C) Feed Water / Air Inlet	50A

Material Specifications	
Description	Material
Casing	uPVC
Cap & Sockets	uPVC
Potting (Adhesive)	Epoxy
O-ring	EPDM

Please contact Toray for more detailed drawing and dimensions.



Toray accepts no responsibility for results obtained by the application of this information or the safety or suitability of Toray's products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each product combination for their own purposes.

All data may change without prior notice, due to technical modifications or production changes. Please be sure to inquire about the latest product specifications.

Headquarters

Japan +81 3 3245 4542

Asia Pacific

China (TBMC) +86 10 8048 5216
Singapore (TAS) +65 6226 0525
Korea (TAK) +82 2 3279 7365

Americas (TMUS)

USA +1 (858) 218 2360

Europe & Sub-Saharan Africa (TMEU)

Switzerland +41 61 415 8710

Middle East (TMME)

Saudi Arabia +966 13 568 0091
U.A.E. +971 4 392 8811



LinkedIn



YouTube

For more info, please visit
water.toray