

HFUG-2020HN

Pressurized Outside to In / Dead-end Filtration Ultrafiltration (UF) Membrane Module

The HFUG-2020HN module is Toray's latest UF innovation that features hollow fibers with a smaller diameter but with improved membrane durability and performance. The result is an increased surface area per module for more production output. The HFUG-2020HN module is a high-pressure resistant UF membrane module ideal for direct coupling to a RO system.

Membrane Characteristics	Unit	Value
Membrane Material		PVDF (Polyvinylidene fluoride)
Nominal Pore Size	μm	0.01
Outer Membrane Surface Area	m ² (ft ²)	90 (969)
Operating Parameters	Unit	Value
Maximum Feed water / Filtrate Flow	m ³ /h (gpm)	15 (66)
Maximum Backwash Flow	m ³ /h (gpm)	16.8 (74)
Maximum Air Flow	Nm ³ /h (scfm)	9.0 (5.3)
Maximum Inlet Pressure	kPa (psi)	600 (87.0)
Maximum Backwash Pressure	kPa (psi)	300 (43.5)
Normal Operating Transmembrane Pressure	kPa (psi)	0–200 (0–29)
Operating Temperature Range	°C (°F)	1–40 (34–104)
pH Range	During Filtration	1–10
	During Cleaning	0–12

*Please contact Toray for operating manual and preliminary design, as capacity per module is highly dependent on feed water quality.



Applications


Drinking water, Industrial process water, Pretreatment for seawater RO desalination, Secondary and Tertiary wastewater

HFUG-2020HN

Pressurized Outside to In / Dead-end Filtration Ultrafiltration (UF) Membrane Module

Dimensions and Weight		Unit	Value
Diameter		mm (in)	216 (8.5)
Length		mm (ft)	2,160 (7.087)
Weight	Full of Water	kg (lbs)	103 (227)
	After Draining	kg (lbs)	65 (143)
Connections		Value	
(1) Filtrate / Backwash		Housing type joint, 80A	
(2) Air Out		Housing type joint, 65A	
(3) Feed Drain / Air In		Housing type joint, 80A	
Material Composition			
Casing		uPVC	
Cap		uPVC	
Potting		Epoxy resin	
O-ring		EPDM	

Please contact Toray for more detailed drawing and dimensions.



Toray accepts no responsibility for results obtained by the application of this information or the safety or suitability of Toray's products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each product combination for their own purposes.

All data may change without prior notice, due to technical modifications or production changes. Please be sure to inquire about the latest product specifications.

Headquarters

Japan +81 3 3245 4542

Asia Pacific

China (TBMC) +86 10 8048 5216
Singapore (TAS) +65 6226 0525
Korea (TAK) +82 2 3279 7365

Americas (TMUS)

USA +1 (858) 218 2360

Europe & Sub-Saharan Africa (TMEU)

Switzerland +41 61 415 8710

Middle East (TMME)

Saudi Arabia +966 13 568 0091
U.A.E. +971 4 392 8811



LinkedIn



YouTube

For more info, please visit

water.toray